

RYTEC

HIGH PERFORMANCE DOORS

FAST-SEAL[®]

HIGH PERFORMANCE ROLLING DOOR



Shown with optional wind bars

FAST-SEAL[®]

The Door that Revolutionized the Industry

When it was introduced with the first-ever Break-Away™ bottom bar, the Fast-Seal high-speed rolling door changed the industry forever. Suddenly, a roll door was able to take a hit without suffering damage.

It is this concept around which the industry has grown, but no other manufacturer has matched the dependability or durability of the Fast-Seal with the original Break-Away bottom bar. Along with its patented counterbalance and tension system, the Fast-Seal remains the best exterior high-speed fabric roll door on the market today.



Shown with optional windows



Break-Away bottom bar

High Speed

- Opening speed of up to 50 inches per second helps improve traffic flow

Safety Focused

- Dual photo eyes in side columns
- Bottom bar reversing edge

Takes a Hit™

- Patented Break-Away bottom bar resets in just seconds

System II[®]

- Independent design permits effective break away
- Provides ability to handle high wind loads and negative pressure

Ry-Wi[®] Wireless System

- State-of-the-art wireless technology eliminates coil cords
- Two-way communication with total frequency control ensure safety

Low Maintenance

- System II comes with a lifetime warranty on all counterweights and tension springs

QUALITY. PERFORMANCE. RELIABILITY.

RYTECDOORS.COM

FAST-SEAL[®]

HIGH PERFORMANCE ROLLING DOOR



Food and Beverage



Heavy Equipment



Warehousing & Distribution



Government & Municipalities



Parking

Size/Dimensions

- Up to 35'W x 24'H
- 12", 14" & 17" Side Column Configurations

Travel Speed

- Opening speed up to 50 inches per second

Operation

- Patented System II[®] design separates counterbalance and fabric tension
- Power drive system with electric motor/brake
- Counterbalance system consists of guided counterweights custom-sized to provide proper balancing of each door
- Independent tension system maintains constant panel tension




Side column with patented System II[®]

Construction

- Fully bolt together, reinforced side frames
- Full-height vinyl door seals
- Vinyl loop seal on bottom bar

Electrical Controls

- System 4[®] controller housed in a NEMA 4x rated enclosure with factory set parameters
- Intelligent processor monitors and controls power consumption
- Advanced self-diagnostics for troubleshooting



System 4 shown with optional rotary disconnect

Panel Design

- 85.5 oz, 3-ply Rilon[™] material
- Vertically flexible, but laterally stiff material helps door panel remain within the guides even if there is wind or pressure
- Puncture-resistant, polymer-impregnated monofilament polyester fabric

Break-Away[™] Bottom Bar

- Patented heavy-duty Break-Away end brackets allow the wireless bottom bar to release in either direction without damaging the door
- Dual cut-off switches automatically shut off motor when bottom bar is impacted
- Bottom bar can be reassembled without tools



Safety

- Standard Pathwatch[®] Safety Light System
- Standard dual thru-beam photo eyes
- Standard sensitivity-adjustable pneumatic reversing edge
- Standard Ry-Wi[®] Wireless System

Warranty

- One-year limited warranty on mechanical and electrical components
- Five-year limited warranty on 3-ply Rilon[™] panel material



Options

- 2-ply Rilon door panel
- 17" or 24" removable windows or screens
- Full screen door panel
- Hood cover, flat or slant
- Wind bars
- Severe duty motor



Full screen panel shown

Standard maximum sizes shown; larger sizes may be available upon request.

American Owned, American Made



◀ Watch All Rytec Testimonials

Specifications subject to change
© 2018 Rytec Corporation LIT013108

RytecDoors.com
888-GO-RYTEC

info@rytecdors.com
P: 262.677.9046 F: 262.677.2058
One Cedar Parkway, PO Box 403
Jackson, WI 53037-0403

RYTEC
HIGH PERFORMANCE DOORS